STRAIGHT RADIATOR HOSE

APPLICATION: FOR USE IN ENGINE COOLANT SYSTEMS.
RESISTANT TO ANTIFREEZE AND CORROSION INHIBITORS

TECHNICAL SPECIFICATION

TUBE: SMOOTH BLACK EPDM RUBBER
COVER: WRAPPED BLACK EPDM RUBBER
REINFORCEMENT: RAYON CORD
TEMPERATURE RANGE: -40^{0}C + 120^{0}C INTERMITTANT 125^{0}C
CONFORMING TO STANDARD: SAE J30 R3
SAFETY FACTOR: 3 x W.P.
BRANDING:WHITE INK "RADIATOR HOSE __ MM I.D "

I.D		O.D	W.P		WEIGHT	MAX COIL	CODE
MM	INS	MM	PSI	BAR	KG/M	M	
13	1/2	22	72	5	0.25	1	RH-013
16	5/8	25	72	5	0.28	1	RH-016
19	3/4	28	72	5	0.3	1	RH-019
22	7/8	30	72	5	0.35	1	RH-022
25	1	34	72	5	0.42	1	RH-025
28	1 1/8	37	72	5	0.52	1	RH-028
30		38	72	5	0.52	1	RH-030
32	1 1/4	41	72	5	0.55	1	RH-032
35	1 3/8	43	72	5	0.59	1	RH-035
38	1 1/2	47	72	5	0.64	1	RH-038
41	1 5/8	49	72	5	0.72	1	RH-041
45	1 3/4	54	72	5	0.75	1	RH-045
48	1 7/8	56	72	5	0.80	1	RH-048
51	2	60	72	5	0.84	1	RH-051
54	2 1/8	63	72	5	0.90	1	RH-054
57	2 1/4	66	72	5	0.95	1	RH-057
60	2 3/8	68	72	5	1.0	1	RH-060
63	2 1/2	72	72	5	1.04	1	RH-063
70	2 3/4	78	72	5	1.15	1	RH-070
76	3	85	72	5	1.45	1	RH-076
80		91	72	5	1.50	1	RH-080
90	3 1/2	102	72	5	1.60	1	RH-090
102	4	114	72	5	1.71	1	RH-102
115	4 1/2	123	72	5	1.83	1	RH-115
127	5	135	72	5	2.02	1	RH-127
140	5 1/2	154	72	5	2.2	1	RH-140
152	6	161	72	5	2.41	1	RH-152