HOSE WORLD

CAR HEATER HOSE

APPLICATION: TRANSPORT OF HOT WATER IN VEHICLE HEATING AND COOLANT SYSTEMS.
RESISTANT TO GLYCOL BASED ANTIFREEZE AND MOST CORROSION INHIBITORS

TECHNICAL SPECIFICATION

TUBE: SMOOTH BLACK EPDM RUBBER
COVER: SMOOTH BLACK EPDM RUBBER
REINFORCEMENT: POLYESTER CORD
TEMPERATURE RANGE: -30^{0}C + 120^{0}C
CONFORMING TO STANDARD: SAE 20R3 C (212)
SAFETY FACTOR: 3 x W.P.
BRANDING: WHITE INK "CAR HEATER HOSE SAE20 R3 C (212) 130 PSI 9 BAR WP __ MM ID "
COLOUR OPTION: BLACK.

I.D		O.D	W.P		BEND RADIUS	WEIGHT	MAX COIL	CODE
MM	INS	MM	PSI	BAR	MM	KG/M	M	
10	3/8	20	130	9	100	0.24	100	CHH-10
13	1/2	21	130	9	130	0.30	100	CHH-13
16	5/8	23	130	9	160	0.36	50	CHH-16
19	3/4	27	130	9	190	0.42	50	CHH-19
22	7/8	32	130	9	220	0.50	40	CHH-22
25	1	33	130	9	250	0.56	50	CHH-25
28	1 1/8	37	130	9	192	0.64	40	CHH-28