CLEAR PVC DUCTING

APPLICATION: LIGHTWEIGHT CLEAR PVC DUCTING
VERY FLEXIBLE & LONG FLEXLIFE
FOR AIR, DUST, FUMES

TECHNICAL SPECIFICATION

BODY: 0.6MM THICK CLEAR PVC
REINFORCEMENT: WHITE PVC COATED WIRE HELIX
TEMPERATURE RANGE: -15^{0}C + 65^{0}C

I.D		PRESSURE	VACUUM	BEND RADIUS	WEIGHT	MAX COIL	CODE
MM	INS	BAR	MMHG	MM	KG/M	M	
20	3/5	0.60	650	20	0.15	10	CPD-20
25	1	0.58	625	25	0.17	10	CPD-25
32	1 1/4	0.53	600	32	0.195	10	CPD-32
38	1 1/2	0.45	550	38	0.285	10	CPD-38
51	2	0.80	400	51	0.350	10	CPD-51
63	2 1/2	0.60	300	63	0.45	10	CPD-63
76	3	0.50	300	76	0.54	10	CPD-76
90	3 1/2	0.40	220	90	0.625	10	CPD-90
102	4	0.40	200	102	0.715	10	CPD-102
127	5	0.30	160	127	0.88	10	CPD-127
152	6	0.22	110	152	1.05	10	CPD-152