HOSE WORLD LTD
UNIT 3,
ACREDALE INDUSTRIAL ESTATE,
EYEMOUTH
TD14 5LQ

TEL: 01890 752555
FAX: 01890 751789
Email: info@hoseworld.com

DATA SHEET: DAIRY WASHDOWN HOSE

APPLICATION

DELIVERY OF HOT WATER & STERILIZING CHEMICALS IN DAIRY AND HYGIENIC ENVIRONMENT

TECHNICAL SPECIFICATION

TUBE: SMOOTH WHITE FDA APPROVED EPDM RUBBER.
PHTHALATE FREE.
COVER: SMOOTH BLUE NON-MARKING EPDM RUBBER
RESISTANT TO ABRASION, WEATHERING
REINFORCEMENT: POLYESTER CORD
TEMPERATURE RANGE: -30^{0}C to +100^{0}C. Not for use with steam
BURST PRESSURE: MINIMUM 3 x W.P.
BRANDING: Black ink:

HOT WATER WASHDOWN HOSE MAX TEMP 100C 10BAR (300PSI) W.P…….MM I.D.

I.D		O.D	W.P		BEND RADIUS	WEIGHT	MAX COIL	CODE
MM	INS	MM	PSI	BAR	MM	KG/Mtr	Mtr	
10	3/8	19	150	10	100	0.329	100	DWH-10-BLUE
13	1/2	23	150	10	130	0.453	100	DWH-13-BLUE
16	5/8	28	150	10	160	0.664	100	DWH-16-BLUE
19	3/4	31	150	10	190	0.755	100	DWH-19-BLUE
25	1	37	150	10	250	1.404	100	DWH-25-BLUE