



**HOSE WORLD**

## EPDM CHEMICAL SUCTION HOSE



**APPLICATION:** SUCTION & DISCHARGE OF VARIOUS CHEMICALS  
(PLEASE ENQUIRE FOR DETAILS),

### TECHNICAL SPECIFICATION

**TUBE:** SMOOTH BLACK ELECTRICALLY CONDUCTIVE EPDM RUBBER

**COVER:** WRAPPED BLACK EPDM RUBBER

**REINFORCEMENT:** POLYESTER CORD AND STEEL WIRE HELIX WITH ANTISTATIC  
COPPER WIRES

**TEMPERATURE RANGE:** -35<sup>0</sup>C + 95<sup>0</sup>C

**CONFORMS TO:** EN12115

**SAFETY FACTOR:** 4 x W.P.

**BRANDING:**BLACK INK ON BLUE STRIPE "EPDM ANTI-STATIC CHEMICAL SUCTION HOSE  
16 BAR W.P EN12115"

I.D		O.D	W.P		BEND RADIUS	VACUUM	WEIGHT	MAX COIL	CODE
MM	INS	MM	PSI	BAR	MM	BAR	KG/M	M	
25	1	37	150	10	152	0.78	0.85	60	CSD-025
32	1 1/4	44	150	10	192	0.78	1.05	60	CSD-032
38	1 1/2	51	150	10	228	0.78	1.22	60	CSD-038
51	2	66	150	10	305	0.78	1.63	60	CSD-051