



HOSE WORLD

ANTI-STATIC SHOTBLAST HOSE



APPLICATION: TRANSPORT OF ABRASIVE MATERIALS IN SAND AND SHOTBLASTING EQUIPMENT.

TECHNICAL SPECIFICATION

TUBE: SMOOTH BLACK ELECTRICALLY CONDUCTIVE ABRASION RESISTANT NR/BR RUBBER
ABRASION RESISTANCE TO DIN 53516 55mm³

COVER: WRAPPED BLACK ELECTRICALLY CONDUCTIVE NR RUBBER

REINFORCEMENT: MULTIPLE TEXTILE PLIES

TEMPERATURE RANGE: -25°C + 70°C

CONFORMING TO STANDARD: BS 5121 , ISO 3861

SAFETY FACTOR: 3 x W.P.

BRANDING: RED INK "ANTI- STATIC SHOTLAST HOSE 12 BAR W.P BS5121 ISO3861 "

I.D		O.D	W.P		BEND RADIUS	WEIGHT	MAX COIL	CODE
MM	INS	MM	PSI	BAR	mm	KG/M	M	
13	1/2	29	175	12	65	0.63	60	ASSBH-13/29
16	5/8	35	175	12	90	1.04	60	ASSBH-16/35
19	3/4	35	175	12	95	0.87	60	ASSBH-19/35
25	1	39	175	12	125	1.00	60	ASSBH-25/39
25	1	48	175	12	135	1.40	60	ASSBH-25/48
32	1 1/4	48	175	12	160	1.20	60	ASSBH-32/48
32	1 1/4	54	175	12	160	1.80	60	ASSBH-32/54
38	1 1/2	56	175	12	190	1.85	60	ASSBH-38/56
38	1 1/2	60	175	12	225	1.95	60	ASSBH-38/60
45	1 3/4	61	175	12	225	2.30	40	ASSBH-45/61
51	2	68	175	12	255	2.00	40	ASSBH-51/68
51	2	71	175	12	255	2.10	40	ASSBH-51/71
60	2 3/8	80	175	12	300	2.40	40	ASSBH-60/80