



HOSE WORLD

FLEXIBLE NYLON TUBE (METRIC)



APPLICATION: WIDE RANGE OF INDUSTRIAL & HYDRAULIC APPLICATIONS.
RESISTANT TO FUELS, OILS & GREASES
GOOD CHEMICAL RESISTANCE (SEE CHARTS)

TECHNICAL SPECIFICATION

TUBE: EXTRUDED SMOOTH PA12 NYLON

TEMPERATURE RANGE: -35C to +70C (intermittent to 120C)

COLOUR OPTIONS: NATURAL, **BLACK**, **YELLOW**, **BLUE**, **RED**, **GREEN**

CONFORMS TO: BS 5409 1 & 2; SAE J1394/A; SAE J844/A; DIN 73378; DIN 74323
DIN 74324 (1 & 2);

ALSO AVAILABLE IN SEMI-RIGID & FOOD GRADE & IN 100mtr COILS TO ORDER

O.D	I.D	W.P.		BEND RADIUS	MAX COIL	CODE++
MM	MM	BAR	PSI	MM	M	
3	1.5	63	900	8	30	NY-3/1.5++
4	2	63	900	8	30	NY-4/2
4	2.5	38	550	8	30	NY-4/2.5
4	3	20	300	10	30	NY-4/3
5	3	40	600	10	30	NY-5/3
6	3	60	900	11	30	NY-6/3
6	4	30	450	13	30	NY-6/4
6	4.5	20	300	13	30	NY-6/4.5
8	5.5	28	400	13	30	NY-8/5.5
8	6	20	300	22	30	NY-8/6
9	6	30	450	26	30	NY-9/6
10	7.5	20	300	26	30	NY-10/7.5
10	8	15	225	50	30	NY-10/8
11	8	20	300	50	30	NY-11/8
12	8	30	450	50	30	NY-12/8
12	9	20	300	45	30	NY-12/9
12	10	12	175	60	30	NY-12/10
13	10	20	300	60	30	NY-13/10
14	10	25	360	60	30	NY-14/10
14	11	18	250	60	30	NY-15/12
15	12	16	230	60	30	NY-15/12
16	12	20	300	85	30	NY-16/12
16	13	15	225	85	30	NY-16/13
18	14	18	260	85	30	NY-18/14
20	16	16	230	85	30	NY-20/16
22	17	18	260	140	30	NY-22/17
25	20	15	225	200	30	NY-25/20
28	22	18	250	200	30	NY-28/22

++= /NAT; /BLA; /BLU; /RED; /GRE; /YEL