



HOSE WORLD

MEDIUM DUTY PVC DUCTING WITH PVC SPIRAL



APPLICATION: SMOOTH BORE UNIVERSAL DUCTING USED FOR CONVEYING VARIOUS FUMES, LIQUIDS, GASES, FIBRES, DUST

TECHNICAL SPECIFICATION

BODY: MEDIUM WEIGHT GREY PVC

REINFORCEMENT: SHOCK PROOF WHITE PVC HELIX

TEMPERATURE RANGE: 0°C + 60°C

I.D. (mm)	WALL THICKNESS (mm)	BEND RADIUS (mm)	VACUUM (m/H ² O)	MAX. LENGTH (mtrs)	WEIGHT Kg/mtr	CODE
20	0.75	30	5	50	0.125	MWP-020
25	0.75	30	5	50	0.150	MWP-025
30	0.80	40	5	50	0.190	MWP-030
32	0.80	40	4.5	50	0.205	MWP-032
35	0.80	45	4.5	50	0.235	MWP-035
38	0.80	45	4.5	50	0.255	MWP-038
40	0.85	50	4	50	0.290	MWP-040
45	0.85	60	4	50	0.360	MWP-045
50	0.85	60	4	50	0.440	MWP-050
55	0.85	65	4	50	0.470	MWP-055
60	0.85	70	4	50	0.500	MWP-060
63	0.90	75	4	50	0.535	MWP-063
70	0.90	85	4	50	0.590	MWP-070
75	0.90	95	4	50	0.640	MWP-075
80	0.95	115	4	50	0.740	MWP-080
90	0.95	130	4	50	0.850	MWP-090
102	1.00	140	4	30	0.970	MWP-100
110	1.00	150	4	30	1.050	MWP-110
120	1.00	160	4	30	1.150	MWP-120
127	1.00	165	4	30	1.240	MWP-127
140	1.10	180	3.5	30	1.440	MWP-140
150	1.10	180	3.5	20	1.700	MWP-150
160	1.15	200	3.5	20	1.900	MWP-160
180	1.15	290	3	20	2.200	MWP-180
200	1.20	380	2.5	20	2.600	MWP-200