



**HOSE WORLD LTD**  
**UNIT 3,**  
**ACREDALE INDUSTRIAL ESTATE,**  
**EYEMOUTH**  
**TD14 5LQ**

**TEL: 01890 752555**  
**FAX: 01890 751789**  
**Email: [info@hoseworld.com](mailto:info@hoseworld.com)**

## **DATA SHEET: WYREM DUCTING**



### **APPLICATIONS**

SUCTION OF CHEMICAL FUMES, INDUSTRIAL DUST, POWDERS AND FOR GENERAL VENTILATION. FOR CHEMICAL RESISTANCE PLEASE CONTACT OUR SALES OFFICE. WYREM IS NOT PRESSURE TIGHT – DO NOT USE IN EXCESS OF 0.35BAR PRESSURE

### **FEATURES**

ROBUST & VERY FLEXIBLE DUCTING WITH EXCELLENT OZONE RESISTANCE AND HIGH VACUUM RATING

### **TECHNICAL SPECIFICATION**

**BODY:** BLACK CORRUGATED 2 PLY CHLOROPRENE (NEOPRENE) COATED COTTON FABRIC WITH ONE FULLY EMBEDDED SPRING STEEL WIRE HELIX AND ONE INTERNAL SPRING STEEL HELIX

**TEMPERATURE RANGE:** -20°C to +100°C

**BRANDING:** YELLOW STRIPE "WYREM"



# HOSE WORLD

## DATA SHEET: WYREM DUCTING

I.D. (mm)	O.D. (mm)	W.P. (Bar)	VACUUM (Bar)	Min. BEND RADIUS (mm)	WEIGHT (Kg/mtr)	Max. LENGTH mtrs	CODE
25	27.4	0.35	0.45	60	0.42	6	WYREM-025
32	34.4	0.35	0.40	63	0.50	6	WYREM-032
38	40.4	0.35	0.40	65	0.57	6	WYREM-038
45	47.4	0.35	0.35	68	0.65	6	WYREM-045
51	53.4	0.35	0.35	71	0.72	6	WYREM-051
60	62.4	0.35	0.35	75	0.75	6	WYREM-060
63	65.4	0.35	0.30	77	0.77	6	WYREM-063
76	78.4	0.35	0.30	84	0.85	6	WYREM-076
80	82.4	0.35	0.25	87	0.88	6	WYREM-080
82	84.4	0.35	0.25	88	0.90	6	WYREM-082
90	92.4	0.35	0.25	93	0.97	6	WYREM-090
102	104.4	0.35	0.20	100	1.10	6	WYREM-102
110	112.4	0.35	0.20	106	1.20	6	WYREM-110
127	129.4	0.35	0.10	119	1.46	6	WYREM-127
152	154.4	0.35	0.10	139	1.92	6	WYREM-152
165	167.4	0.35	0.05	151	2.20	6	WYREM-165
180	182.4	0.35	0.05	166	2.58	6	WYREM-180
203	205.4	0.35	0.05	189	3.23	6	WYREM-203
254	256.4	0.35	0.05	250	4.99	6	WYREM-254
304	306.2	0.35	0.05	319	7.18	6	WYREM-304

ACCESSORIES:  
METAL DUCTING JOINERS  
HOSE CLAMPS