

VACUPRESS OIL SUCTION & DELIVERY HOSE



Application

SUCTION & DELIVERY OF OILS, DIESEL & BIO DIESEL

Technical Specification

Tube:	Smooth Black PU-PVC-Nitrile Rubber Compound
Cover:	Smooth Black PU-PVC-Nitrile Rubber Compound
Reinforcement:	Polyester Cord and Steel Wire Helix Anti-Static Copper Wire in sizes \geq 76mm
Temperature Range:	-30°C to +100°C – Intermittent to 125°C
Vacuum Rating:	9 mH ² O
Burst Pressure:	Minimum 3x W.P.
Branding:	Black Ink on Red Stripe - VACUPRESS OIL -25C +55C VACUUM 9mH ₂ O

I.D		O.D.	WP		MIN BEND RADIUS	WEIGHT	MAX LENGTH	CODE
mm	Ins	mm	psi	Bar	mm	Kg/mtr	mtr	
19		28	230	16	70	0.45	60	VPO-019
25		35	230	16	80	0.64	60	VPO-025
32		42	230	16	100	0.80	60	VPO-032
38		51	200	14	125	1.20	40	VPO-038
45		58	175	12	130	1.34	40	VPO-045
50	-	63	175	12	140	1.73	40	VPO-050
76	-	91	150	10	210	2.70	30	VPO-076
90	-	106	150	10	250	3.25	30	VPO-090
102		118	150	10	300	3.70	30	VPO-102